


Geberit PE T-stuk 45°



Gebruik

- Voor de gebouwfvoer
- Voor terreinafwatering

Kenmerken

- UV-bestendig

Technische gegevens

Materiaal

PE-HD

Artikel

Art. nr.	DN	d, ø [mm]	d1, ø [mm]	H [cm]	X1 [cm]	X2 [cm]	X3 [cm]	K1 [cm]	K2 [cm]	K3 [cm]
360.109.16.1	40 / 40	40	40	13,5	4,5	9	9	2,5	3	3
361.109.16.1	50 / 40	50	40	16,5	5,5	11	11	4	4,5	4,5
361.112.16.1	50 / 50	50	50	16,5	5,5	11	11	3,5	2	2
363.112.16.1	56 / 50	56	50	18	6	12	12	4	3	3
363.115.16.1	56 / 56	56	56	18	6	12	12	4	2,5	2,5
364.109.16.1	60 / 40	63	40	19,5	6,5	13	13	4,5	4,5	4
364.112.16.1	60 / 50	63	50	19,5	6,5	13	13	5	3	3
364.115.16.1	60 / 56	63	56	19,5	6,5	13	13	4,5	2,5	2,5
364.120.16.1	60 / 60	63	63	19,5	6,5	13	13	4	2	2
365.109.16.1	70 / 40	75	40	21	7	14	14	6,5	5	6
365.112.16.1	70 / 50	75	50	21	7	14	14	6	3	4
365.115.16.1	70 / 56	75	56	21	7	14	14	5,5	2,5	3,5
365.120.16.1	70 / 60	75	63	21	7	14	14	4,5	2,5	3,5
365.125.16.1	70 / 70	75	75	21	7	14	14	4	2,5	2,5
366.109.16.1	90 / 40	90	40	24	8	16	16	7,5	5,5	6,5
366.112.16.1	90 / 50	90	50	24	8	16	16	8	4	5
366.115.16.1	90 / 56	90	56	24	8	16	16	7,5	3,5	4,5
366.120.16.1	90 / 60	90	63	24	8	16	16	7	3	4
366.125.16.1	90 / 70	90	75	24	8	16	16	6,5	3	3,5
366.130.16.1	90 / 90	90	90	24	8	16	16	5	2	2
367.109.16.1	100 / 40	110	40	27	9	18	18	9,5	6	7,5
367.112.16.1	100 / 50	110	50	27	9	18	18	9,5	5	5,5
367.115.16.1	100 / 56	110	56	27	9	18	18	9	4	4,5
367.120.16.1	100 / 60	110	63	27	9	18	18	8,5	3,5	4
367.125.16.1	100 / 70	110	75	27	9	18	18	7,5	3	3,5
367.130.16.1	100 / 90	110	90	27	9	18	18	6,5	2,5	3
367.135.16.1	100 / 100	110	110	27	9	18	18	5,5	2	2
368.120.16.1	125 / 60	125	63	30	10	20	20	10,5	4,5	6
368.125.16.1	125 / 70	125	75	30	10	20	20	9,5	4	5
368.130.16.1	125 / 90	125	90	30	10	20	20	8,5	3	3,5
368.135.16.1	125 / 100	125	110	30	10	20	20	7	2,5	2,5
368.139.16.1	125 / 125	125	125	30	10	20	20	6	2	2
369.125.16.1	150 / 70	160	75	37,5	12,5	25	25	13,5	6,5	7,5

369.130.16.1	150 / 90	160	90	37,5	12,5	25	25	12,5	5,5	6,5
369.135.16.1	150 / 100	160	110	37,5	12,5	25	25	11	4,5	5,5
369.139.16.1	150 / 125	160	125	37,5	12,5	25	25	10	4	5
369.145.16.1	150 / 150	160	160	37,5	12,5	25	25	7,5	2,5	2,5
370.125.16.1	200 / 70	200	75	54	18	36	36	18	14	12
370.135.16.1	200 / 100	200	110	54	18	36	36	15	14	6,5
370.139.16.1	200 / 125	200	125	54	18	36	36	14	13	5,5
370.145.16.1	200 / 150	200	160	54	18	36	36	11,5	8,5	3,5
370.146.16.1	200 / 200	200	200	54	18	36	36	8,5	1	1
371.135.16.1	250 / 100	250	110	66	22	44	44	21,5	13,5	15
371.139.16.1	250 / 125	250	125	66	22	44	44	20,5	17,5	14
371.145.16.1	250 / 150	250	160	66	22	44	44	18	13	5
371.146.16.1	250 / 200	250	200	66	22	44	44	15	5	9
371.147.16.1	250 / 250	250	250	66	22	44	44	11,5	5,5	5,5
372.135.16.1	300 / 100	315	110	84	28	56	56	30,5	26	23,5
372.139.16.1	300 / 125	315	125	84	28	56	56	29	25	22
372.145.16.1	300 / 150	315	160	84	28	56	56	27	20,5	20
372.146.16.1	300 / 200	315	200	84	28	56	56	24	12,5	17,5
372.147.16.1	300 / 250	315	250	84	28	56	56	20,5	13	14
372.148.16.1	300 / 300	315	315	84	28	56	56	16	9,5	9,5